

ACTIVE HEAD

The design of this head is universal, as it allows you to change the depth of roll axis depending on the size of the camera. The head is equipped with a digital lens control system that adds functionality and flexibility. It's available with a variety of control options such as Handwheels, Pan Bar, or Joystick.

Features:

- Improved stabilization levels which allows a balanced picture even under extremely rough and difficult operating conditions;
- High angular velocity on all axes;
- Compact Size and Light Weight;
- Fast and effective rebalancing and calibration;
- 360 degree pan and roll function;
- Solid and reliable construction;
- Quick Assembly;
- Remote controlled handling of lens Parameters (Focus, Iris, Zoom).

This model is compatible with a large variety of high profile camera types like ARRI, RED, SONY, PANAVISION etc. and fitting on all types of Cranes, Remote Controlled Platforms and Helicopter/Aerial Systems.

Technical Specifications

Height	895 mm max
Width	745 mm
Depth	630 mm
Power supply AC	220V~ +/-15% *5A max
Power supply DC	19-72 VDC@ 1kW peak
Pan angular speed (max)	200 deg\sec
Tilt angular speed (max)	200 deg\sec
Roll angular speed (max)	200 deg\sec
Pan angular acceleration	600 deg\sec ²
Tilt angular acceleration	800 deg\sec ²
Roll angular acceleration	1000 deg\sec ²
Weight	25 kg

